

**Amendments to the Claims**

The listing of claims below will replace all prior versions and listings of claims in the application. The changes to currently amended claims are shown using strikethrough to identify deleted material and underlining to identify added material.

**Listing of Claims:**

1. (currently amended) An extraction device for extracting an analyte from living tissue through skin, the device comprising:
  - a first electrode part ~~having a contact area with the skin of between 0.01 and 50 mm<sup>2</sup>~~;
  - a through-current electrode part; and
  - a power supply part for supplying electrical energy to the first electrode part and the through-current electrode part to extract an analyte in the first electrode part;
    - wherein the first electrode part comprises a first electrode connected to the power supply part, and a first collection material for collecting an analyte extracted by the first electrode, wherein the first collection material contacts the first electrode; and
    - wherein the first collection material has a contact area with the skin of between about 0.01 and about 25 mm<sup>2</sup>.
2. (canceled)
3. (original) The device of Claim 1, wherein the power supply part supplies a current which flows from the power supply part through the through-current electrode part, the skin, the tissue, and the first electrode part, and returns to the power supply part.
4. (original) The device of Claim 1, wherein the power supply part supplies a current of less than about 300  $\mu$ A.
5. (canceled)

6. (canceled)

7. (original) The device of Claim 1, wherein the first electrode part is detachable from the power supply part.

8. (currently amended) The device of Claim 1, further comprising:

~~a second electrode part having a contact area with the skin of less than about 50 mm<sup>2</sup>~~ comprising a second electrode connected to the power supply part, and a second collection material for collecting an analyte extracted by the second electrode, wherein the second collection material contacts the second electrode;

wherein the power supply part comprises:

a first power supply for supplying electrical energy to the first electrode part and the through-current electrode part, and for extracting an analyte at the first electrode part; and

a second power supply for supplying electrical energy to the second electrode part and the through-current electrode part, and for extracting an analyte at the second electrode part; and

wherein the second collection material has a contact area with the skin of less than about 25 mm<sup>2</sup>.

9. (currently amended) The device of Claim 8, wherein the contact area of the ~~second-electrode part~~ collection material and the skin is between about 0.01 and about 25 mm<sup>2</sup>.

10. (canceled)

11. (original) The device of Claim 8, wherein the first electrode part and the second electrode part are integrated.

12. (original) The device of Claim 1, wherein the power supply part comprises a constant-current power supply.

13. (original) The device of Claim 1, wherein the power supply part comprises a constant-voltage power supply.
14. (original) The device of Claim 1, wherein the power supply part outputs a voltage of less than about 10 V.
15. (original) The device of Claim 1, further comprising an extraction accelerator part for promoting the extraction of the analyte.
16. (original) The device of Claim 15, wherein the extraction accelerator part comprises an ultrasonic irradiation part for irradiating the skin with ultrasonic waves.
17. (original) The device of Claim 1, wherein the analyte is glucose.
18. (original) An analyzer for analyzing an analyte extracted through skin, the analyzer comprising:  
the extraction device of Claim 1;  
an assay part for assaying the analyte extracted in the first electrode part, and for outputting a signal corresponding to an amount of the analyte;  
an analysis part for analyzing the signal output by the assay part to obtain an analysis result; and  
an output part for outputting the analysis result obtained by the analysis part.
19. (currently amended) An extraction device for extracting an analyte in living tissue through skin, the device comprising:  
a first path-forming electrode part ~~having a contact area with the skin of less than 50 mm<sup>2</sup>~~;  
a first extraction electrode part for extracting an analyte;  
a through-current electrode part; and

a power supply part for supplying electrical energy to the first path-forming electrode part, the first extraction electrode part, and the through-current electrode part, for forming analyte transmission paths in the skin for the passage of the analyte, and for extracting the analyte at the first extraction electrode part;

wherein the first path-forming electrode part comprises a first path-forming electrode connected to the power supply part, and a first chamber comprising purified water/ion-conductive material, wherein the purified water/ion-conductive material contacts the first path-forming electrode; and

wherein the first chamber is configured such that the purified water/ion-conductive material has a contact area with the skin of less than about 25 mm<sup>2</sup>.

20. (original) The device of Claim 19, wherein the contact area is between about 0.01 and about 25 mm<sup>2</sup>.

21. (original) The device of Claim 19, wherein the first path-forming electrode part is connected to the power supply part during formation of the analyte transmission paths, and during analyte extraction, wherein the first path-forming electrode part is disconnected from the power supply part, and wherein the first extraction electrode part is connected to the power supply part.

22. (currently amended) The device of Claim 19 further comprising:  
a second path-forming electrode part ~~having a contact area with the skin of less than about 50 mm<sup>2</sup>; and~~

a second extraction electrode part for extracting an analyte;

wherein the power supply part comprises:

a first power supply for supplying electrical energy to the first path-forming electrode part, the first extraction electrode part, and the through-current electrode part, for forming analyte transmission paths in the skin, and for extracting analyte at the first extraction electrode part; and

a second power supply for supplying electrical energy to the second path-forming electrode part, the second extraction electrode part,

and the through-current electrode part, for forming analyte transmission paths in the skin, and for extracting analyte at the second extraction electrode part;

wherein the second path-forming electrode part comprises:

a second path-forming electrode connected to the power supply part; and

a second chamber comprising purified water/ion-conductive material, wherein the purified water/ion-conductive material contacts the second path-forming electrode; and

wherein the second chamber is configured such that the purified water/ion-conductive material has a contact area with the skin of less than about 25 mm<sup>2</sup>.

23. (original) The device of Claim 22, wherein the second path-forming electrode part is connected to the power supply part during formation of the analyte transmission paths, and during analyte extraction, wherein the second path-forming electrode part is disconnected from the power supply part, and wherein the second extraction electrode part is connected to the power supply part.

24. (currently amended) An extraction method for extracting an analyte in living tissue through skin, the method comprising:

placing on the skin a through-current electrode part, and a first electrode part ~~having a contact area with the skin of between 0.01 and 50 mm<sup>2</sup>; and~~

supplying electrical energy to the through-current electrode part and the first electrode part to extract analyte at the first electrode part;

wherein the first electrode part comprises a first electrode connected to the power supply part, and a first collection material for collecting an analyte extracted by the first electrode, wherein the first collection material contacts the first electrode; and

wherein the first collection material has a contact area with the skin of between about 0.01 and about 25 mm<sup>2</sup>.

25. (canceled)

26. (currently amended) The method of Claim 24, further comprising:

placing on the skin a second electrode part ~~having a contact area with the skin of less than about 50 mm<sup>2</sup>; and~~

supplying electrical energy to the through-current electrode part and the second electrode part to extract analyte at the second electrode part;

wherein the second electrode part comprises a second electrode connected to the power supply part, and a second collection material for collecting an analyte extracted by the second electrode, wherein the second collection material contacts the second electrode; and

wherein the second collection material has a contact area with the skin of less than about 25 mm<sup>2</sup>.

27. (original) The method of Claim 26, wherein the placing of the first extraction electrode part on the skin, and the placing of the second extraction electrode part on the skin are executed substantially simultaneously.

28. (original) An analysis method for analyzing an analyte extracted through skin, the method comprising:

extracting an analyte by the method of claim 24;

outputting a signal corresponding to an amount of extracted analyte;

analyzing the signal to obtain an analysis result; and

outputting the analysis result.

29-35. (canceled)

36. (currently amended) The method of claim ~~29~~ 30, wherein the first extraction electrode part ~~has a contact area with the skin of less than about 50 mm<sup>2</sup>~~ comprises a first extraction electrode to which the electrical energy is to be supplied, and a first

collection material, wherein the first collection material contacts the first extraction electrode; and wherein the first collection material has a contact area with the skin of less than about 25 mm<sup>2</sup>.

37. (currently amended) ~~The method of claim 36,~~ A method for extracting an analyte from living tissue through skin, the method comprising:

forming analyte transmission paths in the skin for the passage of analyte;

placing a through-current electrode part on the skin;

placing a first extraction electrode part on the skin in which the analyte transmission paths are already formed; and

supplying electrical energy to the through-current electrode part and the first extraction electrode part to extract analyte at the first extraction electrode part;

wherein the first extraction electrode part has a contact area with the skin of wherein the contact area is between about 0.01 and about 25 mm<sup>2</sup>.

38. (previously presented) An extraction device for extracting an analyte from living tissue through skin, the device comprising:

a first electrode part having a contact area with the skin of between about 0.01 and about 25 mm<sup>2</sup>;

a through-current electrode part; and

a power supply part for supplying electrical energy to the first electrode part and the through-current electrode part to extract an analyte in the first electrode part.